

CVER, CVES

Edge-Lit LED Exit Sign

FEATURES

- Edgelit exit sign for recessed or surface mounted commercial applications
- Clear, injection molded, dual plaque acrylic with extruded aluminum housing
- Single face with clear background, double face with mirror background
- Energy saving, long-life LED lamps exceeds brightness and uniformity requirements
- Field installed appliqué chevron arrows; 6" letters with 3/4" stroke
- Universal end/ceiling/wall surface mount; recessed ceiling mount 24" hanger bars
- Maintenance-free nickel-cadmium battery with fully automatic charger
- Temperature range: 20°C to 30°C (68°F to 86°F)
- UL 924 Listed



EXIT SIGNS

ORDERING INFORMATION

MODEL	FACES	LETTER COLOR	TRIM/HOUSING FINISH	OPERATION
CVER (recessed) CVES (surface)	1 Single 2 Double*	R Red G Green	N Satin Aluminum	E Emergency

*Provided standard with mirror background.

ELECTRONICS

- Transformer isolation, surge, transient, and low voltage disconnect protection
- 90 minute emergency operation
- Reverse polarity, short circuit and AC lockout protection
- 120/277VAC 60Hz operation, test switch and LED AC-On indicator light

POWER CONSUMPTION

	120VAC	277VAC
Red Emergency Models	4.0W	4.0W
Green Emergency Models	4.5W	4.4W

Wattage figures include LED lamps, transformers and electronics power requirements.

