

EDS, ERS, ESS

Lite²

Emergency Lighting Square Unit

EMERGENCY LIGHTING



FEATURES

- Lensed emergency unit for ceiling mounted commercial applications
- High impact, 5VA flame rated, UV stabilized, white thermoplastic trim frame
- Surface, semi-recessed or fully recessed black thermoplastic housing
- Prismatic lens with polished Alzak reflector
- Single or twin miniature wedge-base lamp configurations
- Maintenance-free lead-acid battery with fully automatic solid state charger
- Temperature range: 20°C to 30°C (68°F to 86°F)
- UL 924 Listed

ORDERING INFORMATION

MODEL	DESCRIPTION
EDS	10 Watts, 1 Lamp
ESS I	10 Watts, 1 Lamp, Spectron Circuitry
EDS-2	14.4 Watts, 2 Lamps
ERS	20 Watts, 1 Lamp
ERS I	20 Watts, 1 Lamp, Spectron Circuitry
ERS-3	30 Watts, 1 Lamp
ERS-2-2	30 Watts, 2 Lamps
ERS-2I-2	30 Watts, 2 Lamps, Spectron Circuitry

OPTIONS
-V Voltmeter ¹
-FRM Fully Recessed Model

¹Not available with -FRM option

ACCESSORIES

MODEL	DESCRIPTION
F-SRM	Semi-recessed mounting kit
WG-MLT	Wire guard

Matching Remote Fixtures

RERS-1-0609	Matching remote fixture — single lamp
RERS-2-0607	Matching remote fixture — twin lamps

SPECIFICATIONS

CATALOG NUMBER	ELECTRICAL							
	OUTPUT VOLTS	OUTPUT WATTS				NO. LAMPS	STANDARD LAMP	REMOTE CAPABILITY
		1.5 HOURS	2 HOURS	3 HOURS	4 HOURS			
EDS, ESS-I	6	10	--	--	--	1	9W	No
ERS, ERS-I	6	20	10	--	--	1	9W	Yes
ERS-3	6	30	22	15	--	1	9W	Yes
EDS-2	6	14.4	--	--	--	2	7.2W	No
ERS-2-2, ERS-2I-2	6	30	22	15	--	2	7.2W	Yes

ELECTRONICS

- 120/277 60 Hz VAC operation, test switch and LED AC-On indicator light
- Transformer isolation, surge, transient and low voltage disconnect protection
- Reverse polarity, short circuit and AC lockout protection

