

EXT

Recessed Gimbal Emergency Light

EMERGENCY LIGHTING



FEATURES

- Recessed emergency unit for suspended ceiling applications
- Extruded aluminum housing includes hanger bar assembly and integral junction box
- Formed aluminum gimbal assembly with white trim ring
- Adjustable (up to 26°) sealed beam type high output halogen lamp
- Maintenance-free lead-acid battery with fully automatic charger
- 120/277 60 Hz VAC operation, test switch and LED AC-On indicator light
- Transformer isolation, surge, transient and low voltage disconnect protection
- Reverse polarity, short circuit and AC lockout protection
- Temperature range: 20°C to 30°C (68°F to 86°F)
- UL 924 Listed

ORDERING INFORMATION

EXT-122-EM-K

MODEL

EXT-122-EM-K

ACCESSORIES

MODEL	DESCRIPTION
WGLX	Wire guard
VRS-4X	Vandal resistant shield with neoprene gasket

SPECIFICATIONS

BASE CATALOG NUMBERS	ELECTRICAL				
	OUTPUT VOLTS	OUTPUT WATTS		STANDARD LAMP	REMOTE CAPABILITY
		1.5 HOURS	2 HOURS		
EXT-122-EM-K	6	8	--	8W HAL	No

