

Side Mount Designer Combination LED Unit

FEATURES

- Side mounted combo unit for commercial applications
- Optional LED based MR-16 lamps available for increased coverage and remote capacity
- High-impact, 5VA flame rated, UV stabilized, white thermoplastic housing
- Universal end/ceiling/wall mount and included canopy
- Fully adjustable, high output, MR16 halogen lamp heads
- Energy saving, long-life LED lamps exceed brightness and uniformity requirements
- Snap-in chevron arrows; 6" letters with 3/4" stroke
- Remote capacity with or without lamp heads
- Maintenance-free lead-acid battery with fully automatic charger
- Temperature range: 20°C to 30°C (68°F to 86°F)
- UL 924 Listed



ORDERING INFORMATION

HCX				-	
MODEL	FACES	LETTER COLOR	HOUSING FINISH		OPTIONS
HCX	U Universal Single/ Double Face	R Red G Green	W White B Black		Blank 5W Halogen lamps O3L 3W LED lamps RC12 12W Remote Capacity (includes lighting heads) ^{1,2} O-RC12 23W Remote Capacity (no lighting heads). Available in white only. ^{1,2}

¹ RC12 and O-RC12 options can be specified with the -O3L option.
Example: HCXURW-O-RC12-O3L

² No lamp-head option only available with remote capacity model

ACCESSORIES

MODEL	DESCRIPTION
WGTW	Wire guard (wall or ceiling mount)

MATCHING REMOTE HEADS

MATCHING 5W INDOOR REMOTE HEADS	
CPRSW0605	Single, White
CPRDW0605	Double, White
CPRSB0605	Single, Black
CPRDB0605	Double, Black
MATCHING 5W OUTDOOR REMOTE HEADS	
OCRSW0605	Single, White
OCRDW0605	Double, White
OCRSB0605	Single, Black
OCRDB0605	Double, Black
OCRSZ0605	Single, Dark Bronze
OCRDZ0605	Double, Dark Bronze
MATCHING 3W LED REMOTE HEADS	
OCRSW0603L	Single, White
OCRDW0603L	Double, White
OCRSB0603L	Single, Black
OCRDB0603L	Double, Black
OCRSW1203L	Single, White
OCRDW1203L	Double, White
OCRSB1203L	Single, Black
OCRDB1203L	Double, Black

ELECTRONICS

- Transformer isolation, surge, transient, and low voltage disconnect protection
- Pre-stripped pigtail leads
- 90 minute emergency operation
- Reverse polarity, short circuit and AC lockout protection
- 120/277VAC 60Hz operation, test switch and LED AC-On indicator light

POWER CONSUMPTION

	120VAC	277VAC
Red, Green Models	4.5W	4.5W

Power factor, average: .80 (lagging)
Wattage figures include LED lamps, transformers and electronics power requirements.

