

LED

Aluminum LED Exit Sign

EXIT SIGNS



FEATURES

- Formed aluminum exit sign for light industrial or commercial applications
- Vinyl clad aluminum housing with polycarbonate shield and matching canopy
- Universal end/ceiling/wall mount in multiple finishes
- User selectable constant on or flashing illumination in emergency mode
- Energy saving, long-life LED lamps exceed brightness and uniformity requirements
- Snap out chevron arrows; 6" letters with 3/4" stroke (non-diffused)
- Maintenance-free, lead-acid battery with fully automatic charger
- Temperature range: 10°C to 40°C (50°F to 104°F)
- UL 924 Damp Location Listed

ORDERING INFORMATION

LED	FACES	OPERATION	LETTER COLOR	HOUSING FINISH	OPTIONS
LED	1 Single 2 Double	AC AC Only EM Emergency	R Red G Green	WW White WA White with Brushed Aluminum Face B Black BA Black with Brushed Aluminum Face TT Brass ZZ Antique Brass	2C 2-circuit operation ^{2,5} FAP Fire alarm panel interface ^{3,5,6} DC Remote DC operation ^{2,4,5} TR Tamper resistant screws BPR Beeper module ^{1,6}

¹For use with emergency models only.
²For use with AC models only.
³Operates with 24-volt AC or DC fire alarm panels.
⁴For emergency illumination of sign from remote 12-48 VDC power sources.
⁵DC option may not be specified with -2C or -FAP options.
⁶BPR and FAP options may not be specified together.

ACCESSORIES

MODEL	DESCRIPTION
VRS3	Vandal resistant shield
WGTC	Wire guard (Ceiling/End mount)
WGTW	Wire guard (Wall mount)

DISCHARGE TIMES

	SINGLE FACE	DOUBLE FACE
Flashing Mode	12 Hours	8 Hours
Constant On Mode	6 Hours	4 Hours



A	B	C	D	E	F	G	H
7½"	8.0"	3⅞"	12⅛"	12⅝"	½"	6.0"	4¼"
19 cm	20 cm	7.9 cm	30.8 cm	32.1 cm	1.3 cm	15.2 cm	10.8 cm

ELECTRONICS

- Transformer isolation, surge, transient, and low voltage disconnect protection
- Pre-stripped pigtail leads
- Up to 12 hours of emergency operation
- Reverse polarity, short circuit and AC lockout protection
- 120/277VAC 60Hz operation, test switch and LED AC-On indicator light

POWER CONSUMPTION

	SINGLE FACE MODELS		DOUBLE FACE MODELS	
	120VAC	277VAC	120VAC	277VAC
Red AC Only Models	4.5W	4.5W	6.8W	6.8W
Green AC Only Models	4.7W	4.7W	6.7W	6.7W
Red Emergency Models	5.0W	5.0W	7.3W	7.3W
Green Emergency Models	5.0W	5.0W	7.7W	7.7W

Power factor, average: .8 (lagging)

Wattage figures include LED lamps, transformers and electronics power requirements.

