

Low-Profile Aluminum LED Exit Sign

FEATURES

- Formed aluminum exit sign for light industrial or commercial applications
- Low profile, marine grade vinyl clad aluminum housing and matching canopy
- Universal end/ceiling/wall mount in multiple finishes
- Energy saving, long-life LED lamps exceed brightness and uniformity requirements
- Snap out chevron arrows; 6" letters with 3/4" stroke
- Maintenance-free, nickel-cadmium battery with fully automatic charger
- Temperature range: 10°C to 40°C (50°F to 104°F)
- UL 924 Damp Location Listed



EXIT SIGNS

ORDERING INFORMATION

LEDS	FACES	OPERATION	LETTER COLOR	HOUSING FINISH	OPTIONS
MODEL LEDS	1 Single 2 Double U Universal Single/Double	AC AC Only EM Emergency	R Red G Green	WW White WA White with Brushed Aluminum Face B Black BA Black with Brushed Aluminum Face TT Brass ZZ Antique Brass	TR Tamper resistant screws

ELECTRONICS

- Transformer isolation, surge, transient, and low voltage disconnect protection
- Pre-stripped pigtail leads
- 90 minute emergency operation
- Reverse polarity, short circuit and AC lockout protection
- 120/277VAC 60Hz operation, test switch and LED AC-On indicator light

ACCESSORIES

MODEL	DESCRIPTION
VRS3	Vandal resistant shield
WGLX	Wire guard (Wall mount)
WGLXC	Wire guard (Ceiling Mount)
WGLXE	Wire guard (End mount)

POWER CONSUMPTION

	120VAC	277VAC
Red AC Only Models	3.0W	3.2W
Green AC Only Models	2.8W	2.9W
Red Emergency Models	3.2W	3.3W
Green Emergency Models	3.1W	3.0W

Power factor, average: .8 (lagging)
Wattage figures include LED lamps, transformers and electronics power requirements.



A	B	C	D	E	F	G	H
7½	8.0"	1⅝"	12⅞"	12⅝"	½"	6.0"	4¼"
19 cm	20 cm	4.1 cm	30.8 cm	32.1	1.3 cm	15.2 cm	10.8 cm

