

Wet Location/NEMA 4X Thermoplastic

FEATURES

- Exit sign for wall mounting in harsh applications or industrial environments
- High-impact, corrosion resistant, gasketed, polycarbonate housing with polyamide screws
- Neutral grey, water and dust tight, vented enclosure
- Energy saving, long-life LED lamps exceed brightness and uniformity requirements
- Snap-in chevron arrows; 6" letters with 3/4" stroke
- Maintenance-free nickel-cadmium battery with fully automatic charger
- Temperature range: 0°C to 40°C (32°F to 104°F), EM: 10°C to 40°C (50°F to 104°F)
- UL 924 Wet Location Listed/UL type 50 4X rated (AC models only)



EXIT SIGNS

ORDERING INFORMATION

LN4X		W			-
MODEL LN4X	LETTER COLOR R Red G Green	EXIT FACE COLOR W White	OPERATION Blank AC Only E Emergency	SELF-DIAGNOSTIC Blank None I Spectron self-testing/self-diagnostic electronics*	OPTIONS 2C 2-circuit operation ^{2,5} FAP Fire alarm panel interface ^{3,5,6} FM Flasher module ^{1,6} DC Remote DC operation ^{2,4,5} TR Tamper-proof cover screws (includes tool)

¹ For use with emergency models only.

² For use with AC models only.

³ Operates with 24-volt AC or DC fire alarm panels.

⁴ For emergency illumination of sign from remote 6-24 VDC power sources.

⁵ DC option may not be specified with 2C or FAP options.

⁶ FM and FAP options may not be specified together.

*For use with emergency models only.

POWER CONSUMPTION

	120VAC	277VAC
Red AC Only Models	2.6W	2.6W
Green AC Only Models	2.1W	2.1W
Red Emergency Models	3.8W	3.8W
Green Emergency Models	3.5W	3.5W

Power factor, average: .8 (lagging)

Wattage figures include LED lamps, transformers and electronics power requirements.

ELECTRONICS

- Transformer isolation, surge, transient, and low voltage disconnect protection
- Pre-stripped pigtail leads with push in wiring connectors
- 120 minute emergency operation
- Reverse polarity, short circuit and AC lockout protection
- 120/277VAC 60Hz operation, test switch and LED AC-On indicator light

