

Designer Emergency Lighting Unit 15W to 65W

FEATURES

- Emergency lighting unit for commercial applications
- High impact, 5VA flame rated, UV stabilized, white thermoplastic housing
- High-output halogen lamps in adjustable eyeball style unit (optional LED lamps)
- Remote capacity up to 65 watts
- Maintenance-free battery with fully automatic charger
- 120/277 60 Hz VAC operation, test switch and LED AC-On indicator light
- Transformer isolation, surge, transient and low voltage disconnect protection
- Reverse polarity, short circuit and AC lockout protection
- Temperature range: 20°C to 30°C (68°F to 86°F), damp: 10°C to 40°C (50°F to 104°F)
- UL 924 Listed (optional damp location listed)



EMERGENCY LIGHTING

ORDERING INFORMATION

MODEL	CAPACITY	BATTERY TYPE	RATING	OUTPUT VOLTS	SELF DIAGNOSTICS	OPTIONS
LZ	15 15 Watts ⁴ 20 20 Watts ⁵ 25 25 Watts 30 30 Watts ² 35 35 Watts ^{2,6} 55 55 Watts ² 65 65 Watts ^{2,6}	Blank Lead-Calcium N Nickel-Cadmium ³	Blank Standard Model D Damp Location Listing ⁷	Blank 6 Volts 12V 12 Volts	Blank None I Spectron Self-test/Self-diagnostic Electronics	B Black Finish V Voltmeter 03L 3W LED lamps 10W 10-Watt Halogen Lamps ¹ O Unit Supplied Without Lampheads 24K 220-240VAC, 60Hz ² A31 Auxiliary 3-Conductor Line Cord (120V only)

¹Available on units with capacities of 20 watts or more.
²Not available with Nickel-Cadmium battery models
³Available only on 15, 20 or 25 Watt models
⁴Available only with Ni-Cad and Damp location in 6VDC only
⁵Not available with lead-calcium battery models
⁶Not available with damp-location models
⁷Not available with -03L(LED) option

SPECIFICATIONS

Standard Models

BASE CATALOG NUMBER	OUTPUT VOLTS	BATTERY TYPE	ELECTRICAL						STANDARD LAMP	REMOTE CAPABILITY
			OUTPUT WATTS				5W HAL	Yes		
			1.5 HOURS	2 HOURS	3 HOURS	4 HOURS				
LZ30	6	Lead-Calcium	30	24	15	12	5W HAL	Yes		
LZ35-12V	12	Lead-Calcium	35	26	18	14	5W HAL	Yes		
LZ65	6	Lead-Calcium	65	49	33	26	5W HAL	Yes		
LZ65-12V	12	Lead-Calcium	65	49	33	26	5W HAL	Yes		
LZ20N	6	Nickel-Cadmium	20	15	10	8	5W HAL	Yes		
LZ25N-12V	12	Nickel-Cadmium	25	19	13	10	5W HAL	Yes		

Damp Location Models

BASE CATALOG NUMBER	OUTPUT VOLTS	BATTERY TYPE	ELECTRICAL						STANDARD LAMP	REMOTE CAPABILITY
			OUTPUT WATTS				5W HAL	Yes		
			1.5 HOURS	2 HOURS	3 HOURS	4 HOURS				
LZ25D	6	Lead-Calcium	25	19	13	10	5W HAL	Yes		
LZ30D-12V	12	Lead-Calcium	30	24	15	12	5W HAL	Yes		
LZ55D	6	Lead-Calcium	55	42	28	22	5W HAL	Yes		
LZ55D-12V	12	Lead-Calcium	55	42	28	22	5W HAL	Yes		
LZ15ND	6	Nickel-Cadmium	15	11	8	6	5W HAL	Yes		
LZ20ND-12V	12	Nickel-Cadmium	20	19	13	10	5W HAL	Yes		

ACCESSORIES

MODEL	DESCRIPTION
VRS	Vandal resistant shield
WGEL	Wire Guard

MATCHING INDOOR REMOTE FIXTURES

WHITE		BLACK		VOLTS	WATTS
SINGLE	TANDEM	SINGLE	TANDEM		
LZRSW0605	LZRDW0605	LZRSB0605	LZRDB0605	6	5
LZRSW0610	LZRDW0610	LZRSB0610	LZRDB0610	6	10
LZRSW1205	LZRDW1205	LZRSB1205	LZRDB1205	12	5
LZRSW1210	LZRDW1210	LZRSB1210	LZRDB1210	12	10
LZRSW0603L	LZRDW0603L	LZRSB0603L	LZRDB0603L	6	3
LZRSW1203L	LZRDW1203L	LZRSB1203L	LZRDB1203L	12	3

For other indoor or outdoor remote fixture styles, see the "Remote Heads and Fixtures" section starting on page 953.

