

## New York City Steel Exit

### FEATURES

- Metal exit sign for commercial or light industrial applications
- Designed to meet New York City specifications
- Heavy duty, wall mounted, 20 gauge steel housing
- Universal end/ceiling/wall mount and included canopy
- Energy saving, long-life LED lamps exceeds brightness and uniformity requirements
- Knockout directional chevron arrows; 8" letters with 3/4" stroke
- Maintenance-free nickel-cadmium battery with fully automatic charger
- Temperature range: 0°C to 45°C (32°F to 113°F)
- Listed to UL 924 standards



EXIT SIGNS

### ORDERING INFORMATION


<b>NYX</b>					-	
<b>MODEL</b>	<b>FACES</b>	<b>LETTER COLOR</b>	<b>HOUSING FINISH</b>	<b>OPERATION</b>	<b>OPTIONS</b>	
NYX	U Universal Single/ Double Face	R Red	W White B Black	A AC Only E Emergency	TR Tamper resistant option <sup>1</sup>	

<sup>1</sup>Provides two tamper-resistant locking screws.

### ACCESSORIES

MODEL	DESCRIPTION
PMNYW	Pendant mounting kit (white)
PMNYB	Pendant mounting kit (black)
WGTW	Wire guard (Wall mount)

A	B	C
10½"	14½"	2¾"
26.7 cm	36.8 cm	6.0 cm



\* Add 1" (2.5 cm) for mounting canopy on ceiling or end mounted models

## New York City Combination Unit


### FEATURES

- Top mounted combo unit for commercial applications
- Designed to meet New York City specifications
- Heavy duty, wall mounted, 20 gauge steel housing with two or three lamp heads
- High-impact, 5VA flame rated, UV stabilized, thermoplastic lamp heads
- Energy saving, long-life LED lamps exceeds brightness and uniformity requirements
- Knockout directional chevron arrows; 8" letters with 3/4" stroke
- Maintenance-free lead-acid battery with fully automatic charger
- Available with 2 or 3 adjustable incandescent 7.2W heads
- Temperature range: 0°C to 40°C (32°F to 104°F)
- Listed to UL 924 standards



### ORDERING INFORMATION

<b>NYXC</b>						-	
<b>MODEL</b>	<b>FACES</b>	<b>LETTER COLOR</b>	<b>HOUSING FINISH</b>	<b>OPERATION</b>	<b>NO. OF LIGHTING HEADS</b>		
NYXC	S Single D Double	R Red	W White B Black	E Emergency	2 Two 3 Three		
				<b>OPTIONS</b>			
				0612 12 watt lamps <sup>1,2</sup> TR Tamper resistant option <sup>3</sup>			



A	B	C	D
9⅝"	15½"	15"	4¼"
24.4 cm	39.4 cm	38.1 cm	10.8 cm

### ACCESSORIES

MODEL	DESCRIPTION
40G	Wire guard (wall mount)

<sup>1</sup> 12 watt high-output lamps available on two-headed models only.

<sup>2</sup> Only available with 2 lighting heads.

<sup>3</sup> Provides two stainless steel tamper resistant locking screws.

