

FEATURES

- Die-cast aluminum exit sign for commercial or light industrial applications
- Designed to meet New York City specifications
- Universal end/ceiling/wall mount and included die-cast aluminum canopy
- Energy saving, long-life LED lamps exceeds brightness and uniformity requirements
- Knockout directional chevron arrows; 8" letters with 3/4" stroke
- Maintenance-free nickel-cadmium battery with fully automatic charger
- Temperature range: 0°C to 45°C (32°F to 113°F)
- Listed to UL 924 standards



EXIT SIGNS

ORDERING INFORMATION

NYDC					
MODEL	FACES	LETTER COLOR	HOUSING FINISH	OPERATION	OPTIONS
NYDC	S Single D Double	R Red	W White B Black BN Black with brushed face	A AC Only E Emergency	-FM Flasher module ⁽¹⁾⁽²⁾ -AA Audible alarm module ⁽¹⁾⁽²⁾

(1) For use with emergency models only.
(2) -FM and -AA options may not be specified together.

ACCESSORIES

MODEL	DESCRIPTION
PMNYW	Pendant mounting kit (white)
PMNYB	Pendant mounting kit (black)
WGTW	Wire guard (Wall mount)
WGTC	Wire guard (Ceiling mount)

POWER CONSUMPTION

	120VAC	277VAC
AC Only Models	2.4W	2.4W
Emergency Models	3.4W	3.5W

Wattage figures include LED lamps, transformers and electronics power requirements.

ELECTRONICS

- Transformer isolation, surge, transient, and low voltage disconnect protection
- 90 minute emergency operation
- Reverse polarity, short circuit and AC lockout protection
- 120/277VAC 60Hz operation, test switch and LED AC-On indicator light



* Add 1" (2.5 cm) for mounting canopy on ceiling or end mounted models

A	B	C
11"	16 1/4"	2 5/8"
27.9 cm	41.3 cm	6.7 cm