

Fixed Optic Emergency Light

FEATURES

- Fixed lens emergency unit for commercial applications
- High impact, 5VA flame rated, UV stabilized, white thermoplastic housing
- Glare free acrylic Fresnel lens with T5 incandescent lamps
- Maintenance-free lead-calcium battery with fully automatic charger
- 120/277 60 Hz VAC operation, test switch and LED AC-On
- Transformer isolation, surge, transient and low voltage disconnect protection
- Reverse polarity, short circuit and AC lockout protection
- Temperature range: 20°C to 30°C (68°F to 86°F)
- UL 924 Listed



EMERGENCY LIGHTING

ORDERING INFORMATION

SL1	-	[]
MODEL		OPTIONS
SL1		B Black Housing 6H 6 Watt Halogen Lamps V Voltmeter

ACCESSORIES

MODEL	DESCRIPTION
VRS	Vandal resistant shield
WGEL	Wire guard

SPECIFICATIONS

BASE CATALOG NUMBER	ELECTRICAL							
	OUTPUT VOLTS	OUTPUT WATTS		AC INPUT			STANDARD LAMP	REMOTE CAPABILITY
		1.5 HOURS	2 HOURS	VOLTS	AMPS	WATTS		
SL1, SL1-V	6	12.0	--	120 277	.120 .135	6.0 6.0	5.4W	No

