

FEATURES

- Power pack to maintain the arc of Metal Halide lamps during power disturbances
- Provides two minutes of continuous arc during power sags, interruptions or failure
- Sealed nickel-cadmium battery maintains lamp at 20-30% of normal power
- Can be used with switched or unswitched luminaires
- Installation may be remote of the luminaire
- 120/277VAC 60/50Hz operation, test switch and AC-On indicator light
- Temperature range: 0°C to 55°C (32°F to 131°F)
- UL 924 Damp Location Listed for Auxiliary Lighting



BATTERY PACKS

ORDERING INFORMATION

| MODEL | LAMP TYPE | WATTAGE |
|-------|-------------------|------------------|
| UFO | -MH Probe Start | 175 |
| | -PSMH Pulse Start | 250 ¹ |
| | | 400 |

¹Probe Start Only

SPECIFICATIONS

| CATALOG NUMBER | INPUT WATTAGE | MAX. DISTANCE FROM LAMP | BALLAST TYPE | LAMP TYPE | LAMP WATTAGE |
|----------------|--------------------------------|-------------------------|----------------------------------|-------------|-----------------|
| UFO-MH175 | 6W at 120VAC 10W at 277VAC | 30 | CWA | Probe Start | 150W 175W |
| UFO-MH250 | | 50 | | | 225W 250W |
| UFO-MH400 | | 80 | | | 360W 400W |
| UFO-PSMH175 | 6W at 120 VAC 9W at 277 VAC | Consult Factory | Reactor High Reactance CWA | Pulse Start | 100W to 175W |
| UFO-PSMH400 | | | | | 200W to 400W |

