



# SLM Series

## Self-Luminous Exit Sign With Aluminum Frame

Catalog Number	
Comments	Type

### FEATURES

#### Application

The SLM Series is a self-luminous exit sign which offers continuous illumination with no electrical power required. The exit sign is totally self-contained and offers single or double-face operation with universal chevrons. The SLM Series is ideal for damp, wet and extreme temperature applications.

#### Construction

Single and Double face models are available with aluminum frame and stencil.

#### Installation

The SLM can be wall mounted by use of a mounting plate which is included. For ceiling or end mounting, a universal mounting plate must be ordered separately. The SLM can also be pendant mounted by use of a pendant accessory which must be ordered separately.

#### Illumination

The exit face is illuminated by tritium gas (a natural isotope of hydrogen) which is sealed inside phosphor lined glass tubes. The SLM series has a 10 or 20 year effective service life. Letters are 6" high, 3/4" stroke, standard exit sign. Maximum distance for legibility is 100 feet.

#### Compliances

UL Listed to UL 924 Standard  
NFPA 101 Life Safety Code

#### Warranty

The SLM series is warranted for the full rated service life of the product which is 10 or 20 years depending on model selected.



Aluminum Frame

### ORDERING GUIDE

<b>SLM</b>	<b>S</b>	<b>R</b>	<b>W</b>	<b>10</b>
Series	Faces	Face Color	Housing Finish	Service Life
	S - Single D - Double	R - Red G - Green B - Black Z - Bronze	B - Black W - White N - Brushed Aluminum Z - Bronze	10 - 10 Years 20 - 20 Years

### ACCESSORIES - Order Separately

Part Number	Description
SLPA	12" Swivel Pendant <sup>(1)</sup>
SLPB	24" Swivel Pendant <sup>(1)</sup>
SLPC	36" Swivel Pendant <sup>(1)</sup>
SLPD	48" Swivel Pendant <sup>(1)</sup>
SLM05	Single Face Ceiling/End Mounting Plate
SLM10	Double Face Ceiling/End Mounting Plate

<sup>(1)</sup> Available in black color only.



# SLM Series

*Self-Luminous Exit Sign With Aluminum Frame*

## SPECIFICATIONS

**Operating Temperature:** -55°C to 80°C (-67°F to 176°F)

**Overall Size:** Single Face, 12 <sup>3</sup>/<sub>4</sub>" x 8 <sup>1</sup>/<sub>4</sub>" x 1 <sup>1</sup>/<sub>2</sub>"  
Double Face, 12 <sup>3</sup>/<sub>4</sub>" x 8 <sup>1</sup>/<sub>4</sub>" x 2 <sup>3</sup>/<sub>4</sub>"

**Weight:** Single Face 4.0 lbs.  
Double Face 8.0 lbs.

