



Remote Lighting Heads

Standard Remote Lighting Heads

SRH Series

Injection molded thermoplastic lamphead/round mounting plate assemblies. Mounts to 3½" octagonal or single gang boxes. For use with most commercial or industrial emergency fixtures. Standard finish is available in white or black. Single and twin lamp fixtures with a choice of incandescent or halogen PAR 36 lamps.



ORDERING INFORMATION

SRH			
MODEL	STYLE	FINISH	LAMP
SRH	S Single D Double	W White B Black	0605 6 volt, 5.4 watts Incandescent ¹ 0607 6 volt, 7.2 watts Incandescent ¹ 0608 6 volt, 8 watts Halogen 0612 6 volt, 12 watts Halogen 0618 6 volt, 18 watts Incandescent 0620 6 volt, 20 watts Halogen 0625 6 volt, 25 watts Incandescent 1207 12 volt, 7.2 watts Incandescent ¹ 1208 12 volt, 8 watts Halogen 1212 12 volt, 12 watts Halogen 1218 12 volt, 18 watts Incandescent 1225 12 volt, 25 watts Incandescent 1235 12 volt, 35 watts Incandescent 2409 24 volt, 9 watts Incandescent ¹

¹Sealed Beam Type Lamp

Outdoor Remote Lighting Heads

OMS Series

Outdoor aluminum spot with sealed lamp and swivel assembly. Furnished with round gasketed aluminum mounting plate. Mounts to 3½" octagonal boxes.



ORDERING INFORMATION

OMS			
MODEL	STYLE	FINISH	LAMP
SRH	S Single D Double	W White B Black	0605 6 volt, 5.4 watts Incandescent ¹ 0607 6 volt, 7.2 watts Incandescent ¹ 0608 6 volt, 8 watts Halogen 0612 6 volt, 12 watts Halogen 0618 6 volt, 18 watts Incandescent 0620 6 volt, 20 watts Halogen 0625 6 volt, 25 watts Incandescent 1207 12 volt, 7.2 watts Incandescent ¹ 1208 12 volt, 8 watts Halogen 1212 12 volt, 12 watts Halogen 1218 12 volt, 18 watts Incandescent 1225 12 volt, 25 watts Incandescent 1235 12 volt, 35 watts Incandescent 1250 12 volt, 50 watts Halogen

¹Sealed Beam Type Lamp



Remote Lighting Heads



Decorative Indoor Remote Lighting Heads

CPR Series

Injection molded thermoplastic decorative lamphead and mounting plate assembly. Mounts to 3½" octagonal or single gang boxes. Single and twin lamp fixtures with MR16 lamp included. Standard finish is available in white or black.



Decorative Outdoor Remote Lighting Heads

OCR Series

Outdoor UL Wet Location Listed die cast aluminum lamp head and mounting plate assembly complete with MR 16 lamp. Single or twin lamp fixtures available in dark bronze, black or white polyester powder coat finish. Mounts to 3½" octagonal or single gang boxes. Available with 5 watt lamps. Housing rated up to 50 watts. Lamps higher than 5 watts supplied by others.

ORDERING INFORMATION

MODEL

OCR
CPR

STYLE

S Single
D Double

FINISH

W White
B Black
Z Dark Bronze¹

¹Not available with CPR series

LAMP

0605 6 volt, 5 watt Halogen



Remote Lighting Heads

All Metal Remote Lighting Heads

AHD

Stamped aluminum housing with metal swivel. Standard finish available in white or black. Choice of incandescent or halogen PAR 36 lamps.



ORDERING INFORMATION

AHD			
MODEL	STYLE	FINISH	LAMP
AHD	S Single D Double	W White B Black	0605 6 volt, 5.4 watts Incandescent ¹ 0607 6 volt, 7.2 watts Incandescent ¹ 0608 6 volt, 8 watts Halogen 0612 6 volt, 12 watts Halogen ² 0618 6 volt, 18 watts Incandescent 0620 6 volt, 20 watts Halogen 0625 6 volt, 25 watts Incandescent 1207 12 volt, 7.2 watts Incandescent ¹ 1208 12 volt, 8 watts Halogen 1212 12 volt, 12 watts Halogen ² 1218 12 volt, 18 watts Incandescent 1225 12 volt, 25 watts Incandescent 1235 12 volt, 35 watts Incandescent 1250 12 volt, 50 watts Halogen 2407 24 volt, 7.2 watts Incandescent ¹ 2413 24 volt, 13 watts Incandescent ¹ 2418 24 volt, 18 watts Incandescent ¹ 2428 24 volt, 28 watts Incandescent ¹

¹Sealed Beam Type Lamp

²Not available on Sealed Beam Type Lamps

Environmental Lighting Head

GNX Series

Moisture resistant thermoplastic head in black finish with coated lamp terminals and sealed swivel assembly. Furnished with mounting plate. Available with a choice of incandescent or halogen PAR 36 lamps. Matches N4X series units.



Available with shatter containment option. Add "-L" to model number for Sealed Beam Lamps PAR36 only. Example: GNXSB0625-L



ORDERING INFORMATION

GNX			
MODEL	STYLE	LAMP	OPTIONS
GNX	S Single D Double	0605 6 volt, 5.4 watts Incandescent ¹ 0607 6 volt, 7.2 watts Incandescent ¹ 0608 6 volt, 8 watts Halogen 0612 6 volt, 12 watts Halogen 0618 6 volt, 18 watts Incandescent 0620 6 volt, 20 watts Halogen 0625 6 volt, 25 watts Incandescent 1208 12 volt, 8 watts Halogen 1209 12 volt, 9 watts Incandescent ¹ 1212 12 volt, 12 watts Halogen 1218 12 volt, 18 watts Incandescent 1225 12 volt, 25 watts Incandescent 1235 12 volt, 35 watts Incandescent	-L Shatter Containment ²

¹Sealed Beam Type Lamp

²Not available on Sealed Beam Type Lamps



Remote Lighting Fixtures

Square



RERS

Injection molded housing. Surface mounted. Semi-recessed or recessed mounting available with kit. Black box, white trim. Single (RERS-1) and twin (RERS-2) lamp models. Dimensions and mounting kits same as Lite².

INCANDESCENT WEDGE BASE		
MODEL NUMBERS	LAMP VOLTS	LAMP WATTS
RERS-1-0609	6	9
RERS-2-0607	6	7

MODEL	DESCRIPTION
F-SRM	Semi-recessed mounting kit
-FRM	Fully-recessed option

Recessed Rectangle



124R

Recessed mounted fixture with frosted lens. White trim. Dimensions: 8³/₁₆" x 4¹/₂" x 4"

DC BAYONET BASE		
MODEL NUMBERS	LAMP VOLTS	LAMP WATTS
124R-0628	6	28
124R-1228	12	28

Recessed Eyeball



133

Adjustable to 42° and rotated through 358°. White standard, other finishes upon request. Dimensions: Trim ring: 4⁷/₈" dia. Back box: 4³/₁₆" deep x 4" dia.

DC BAYONET BASE		
MODEL NUMBERS	LAMP VOLTS	LAMP WATTS
133-0618	6	18
133-1228	12	28

Gimbal



122

Adjustable (60° max.) recessed mounted fixture. Matte white trim. Dimensions: 8¹/₂" dia. x 4¹/₂"

INCANDESCENT PAR 36 SEALED BEAM		
MODEL NUMBERS	LAMP VOLTS	LAMP WATTS
122SB-0625	6	25

LZ Series Matching Remote Lighting Heads

LZR

Architectural/commercial design. High performance MR-16 halogen lamps standard. Mounts to standard electrical boxes using universal mounting plate provided. Fixture housing mounts to back plate in a choice of four mounting positions. Housings secured using locking screws provided.



SINGLE REMOTE HEAD - WHITE	SINGLE REMOTE HEAD - BLACK	LAMP VOLTS	LAMP WATTS
LZRSW0605	LZRSB0605	6	5
LZRSW0610	LZRSB0610	6	10
LZRSW1205	LZRSB1205	12	5
LZRSW1210	LZRSB1210	12	10

TWIN REMOTE HEAD - WHITE	TWIN REMOTE HEAD - BLACK	LAMP VOLTS	LAMP WATTS
LZRDW0605	LZRDB0605	6	5
LZRDW0610	LZRDB0610	6	10
LZRDW1205	LZRDB1205	12	5
LZRDW1210	LZRDB1210	12	10

C1D2R/C1D2TR

Suitable for wet and damp location applications. Rated for NEC Class I, Division 2, Groups B, C and D as well as Class I, Zone 2, Group IIB + H₂ environments. Black housing and head assemblies. Single (C1D2R) and twin (C1D2TR) head models.



3R Listed

MODEL NUMBERS		LAMPS*	
SINGLE HEAD HUB LEFT SIDE ^{1,2}	TWIN HEAD HUB LEFT SIDE ^{1,2}	VOLTS	WATTS
C1D2R-6V8W	C1D2TR-6V8W	6	8
C1D2R-6V12W	C1D2TR-6V12W	6	12
C1D2R-12V8W	C1D2TR-12V8W	12	8
C1D2R-12V12W	C1D2TR-12V12W	12	12

* PAR 36 Halogen sealed beam lamps.

¹Hub Right Side — add "R" to end of model number. Example C1D2R-6V8WR.

²Hubs Both Sides — add "F" to end of model number. Example C1D2R-6V8WF.

Replacement lamp part numbers and photometrics are available on the web at www.dual-lite.com.

Dual-Lite Life Safety Products • www.dual-lite.com

A Hubbell Lighting, Inc. brand with representatives' offices in principal cities throughout North America.

Copyright © Hubbell Lighting, Inc., All Rights Reserved • Specifications subject to change without notice. • Printed in U.S.A.



HUBBELL LIGHTING, INC.

0602008 Rev C 6/09